



Gas Fuelled Equipment OPERATING & SAFETY GUIDE



This Appliance is only for professional use by a qualified person

Never use the equipment in a poorly ventilated space. Keep all children, animals and bystanders away from the work area. Ensure the floor of the work area is free from trip hazards and non-slip.

Keep a bucket of water nearby to treat burns. Use a CO₂ extinguisher in case of fire. Wear suitable clothing, such as an apron, overall and hat. Use kitchen/BBQ gloves to handle utensils. Tie back long hair.

Allow the appliance to cool fully before touching or cleaning.

Regulators and valves should make a metal-to-metal gas tight seal or be fitted with a rubber seal. On no account should PTFE tape, thread tape or any other sealant be used to try to secure a gas-tight seal in a leaking connection.

Please go to our safety
information and equipment
operating instructions catalogue
page to download
available on our website
www.angeloeventhire.com

We would have prepared/tested and checked these items prior to you receiving them to ensure safe and full working condition.

GENERAL SAFETY ADVICE

PLEASE READ THESE INSTRUCTIONS CAREFULLY. THERE IS A RISK OF INJURY IF YOU DO NOT FOLLOW THE INSTRUCTIONS IN THIS GUIDE.

The safe use of any hired gas equipment becomes the sole responsibility of the hirer once the items are either collected or arrive on site. Angelo's staff are not permitted to install equipment on site and you are not permitted to make any alterations/modifications to the appliance or connectors in any way.

These instructions are provided so you can familiarise yourself with proper and safe operation of this appliance but are not a substitute for being conversant with duties as hirer under the LPG Code.

If in any doubt please call us for advice or contact a gas engineer conversant with the LPG code

Care of Gas equipment

Ensure the gas cylinder is positioned away from the equipment when it is being used

Some equipment may have a flame cut device, designed to stop gas escaping when the flame is not lit or has blown out, please be aware that not all gas equipment hired has this safety feature installed therefore it is the hirers responsibility to check that the equipment is operating properly during use and that the flame/pilot is engaged, and has not blown out and that the gas is not escaping.

Lighting instructions -

Use separate instructions "lpg safety advice cylinders" available on our website for gas connection instructions.

Items with pilot light - locate pilot light, depress button on flame suspension device, after pilot flame has lit, continue holding flame suspension device until flame has established, then set gas flow as required.

items without pilot light - partial turn gas tap to a relevant ring on, light ring using a lighted taper.